


SCALE 1:1



CABLE STRIPPING DIM.

ELECTRICAL PERFORMANCE:  
 1. IMPEDANCE : 50 OHMS.  
 2. FREQUENCY : 6.0 GHz.  
 3. WORKING VOLTAGE : 170 Vrms MAX.  
 4. DIELECTRIC WITHSTANDING VOLTAGE : 500Vrms MAX.  
 5. INSULATOR RESISTANCE : 1000MEGOHMS MIN.  
 6. VSWR < 1.5 @ 4.0GHz. < 2.0 @ 6.0GHz.

NO.	QTY	DESCRIPTION	PART'S NO.	MATERIAL	FINISH
4	1	FERRULE	12-137R0-05NA	BRASS	NICKEL PLATED
3	1	INSULATOR	12-138R0-0300	TEFLON	NONE
2	1	CONTACT	12-137R0-02GD	BRASS	GOLD PLATED
1	1	INSULATOR	S12-138R0	TEFLON	NONE
	1	RING		BRASS	NICKEL PLATED
	1	BODY		BRASS	NICKEL PLATED

DO NOT SCALE DRAWING	GENERAL TOLERANCES				MATERIAL : SEE TABLE		圓陵工業股份有限公司 ALINER INDUSTRIES, INC.		
	DIM: .X±0.25(0.01) .XX±0.12(0.005)				FINISH : SEE TABLE				
	ANGULAR: ±3'				DRAWN BY: JAY 11/28/2006				
	DIMENSION CLASSIFICATION				CHK'D BY: YVONNE 11/14/2007				
<input type="checkbox"/> MATERIAL CHANGE <input type="checkbox"/> ADD. STAKE		970405 YV. 4-09-08' 961105 YV. 11-14-07'		<input checked="" type="checkbox"/> CRITICAL <input type="checkbox"/> MAJOR		TITLE: RP TNC JACK FOR RG-178 CABLE			
LTR	REVISION RECORD	ECN	DR/CHK	DATE	REVISE ONLY ON CAD SYSTEM	SHEET 1 OF 1	UNIT : mm	DWG. NO.: 12-138R0-B	REV C