

DO NOT SCALE DRAWING

8 7 6 5 4 3 2 1

16.15 REF.

1

1/4-36UNS-2B

12.70

8.50

6.40 MAX.

1.90

7.15 CROSS KNURLED

6.00 ⁺⁰_{-0.15}

2

7.10

NOTE:

FREQ. DC-6 GHz

TORQUE FORCE 200~500 g-cm

I.R. < -1.3 dB @DC TO 6.0 GHz

VSWR < 1.5 @DC TO 6.0 GHz

NO.	QTY	DESCRIPTION	PART'S NO.	MATERIAL	FINISH
2	1	CONTACT	20-002RV-02GB	PHOSPHORUS BRONZE	GOLD PLATED
1/50	1	TRAY		PET	NONE
1	1	BODY		BRASS	NICKEL PLATED
1	1	INSULATOR		TEFLON	NONE
1	1	RING	S20-003RV	BRASS	NICKEL PLATED
1	1	GASKET		SILICON RUBBER	NONE
1	1	RING		BRASS	NICKEL PLATED
1	1	SHELL		BRASS	BLACK CHROME

GENERAL TOLERANCES

DIM: X±0.25(0.01)

ANGULAR: ±3°

XX±0.12(0.005)

MATERIAL: SEE TABLE

FINISH: SEE TABLE

DRAWN BY: MARY 10/26/2005

CHK'D BY:

APP'D BY:

SHEET 1 OF 1

UNIT: mm

SCALE: 5:1

DWG. NO.: 20-003RV-T

REV A

圖陵工業股份有限公司

ALINER INDUSTRIES, INC.

20-003RV

SCALE 1:1